



Ordering code:: VML 340 AM DALI



ELECTRICAL FEATURES

Wattage	40 W
Supply voltage	198 - 264 V AC / 190 - 280 V DC
Power factor	0.98
Total harmonic distortion	<10
IEC Protection Class	I
Energy class	A++
Dimming	DALI
Qty. per MCB C 16A	53 pcs
LED driver lifespan	100 000 hod. @ t _c =65°


OPTICAL FEATURES

Lamp luminous flux	4900 lm
Luminous efficiency	123 lm/W
Color temperature	3K / 4K / 5K
Color rendering index	80+
Chromaticity tolerance	3 step MacAdam
Viewing angle	139°x105°
Unified glare rating	24.2/22.3
Luminance @65° < 3000 cd/m ²	-
LED lifespan	L ₈₀ / B ₁₀ = 100 000 hod. @ 65°C

MECHANICAL FEATURES

Dimensions	1277 x 86 x 95 mm
Weight	2.2 kg
Operating temperature	- 25 ~ + 35 °C
Protection class	IP 65
Body material	polyester + glass fiber
Reflector material	-
Diffuser material	PMMA
Mounting method	přisazená nebo závěsná

POLAR DIAGRAM



ON REQUEST

- CCT 2700K, 3500K, 5700K, 6500K
- CRI > 90Ra
- Customized power
- Through wiring
- Customized cable
- Connectors Gesis GST, RST
- Emergency source 1 hr/3 hrs