

ONTEC R C1U, C2, C5



Type	Wattage	Luminous flux	Lighting time - h	Mode	UGR	A	B	C
STANDARD								
ONTEC R C1U 101 NM ST 1xLED 1h NM	1	122	1	MN	130	130	27	
ONTEC R C1U 301 NM ST 1xLED 3h NM	1	122	3	MN	130	130	27	
ONTEC R C1 102 M ST 1xLED 1h M (NM)	2	233	1	M/MN	130	130	27	
ONTEC R C1 302 M ST 1xLED 3h M (NM)	2	233	3	M/MN	130	130	27	
ONTEC R C2 105 M ST 2xLED 1h M (NM)	5	421	1	M/MN	130	130	27	
ONTEC R C2 305 M ST 2xLED 3h M (NM)	5	421	3	M/MN	130	130	27	
AUTOTEST								
ONTEC R C1 102 M AT 1xLED 1h M (NM)	2	233	1	M/MN	130	130	27	
ONTEC R C1 302 M AT 1xLED 3h M (NM)	2	233	3	M/MN	130	130	27	
ONTEC R C5 105 M AT 2xLED 1h M (NM)	5	421	1	M/MN	130	130	27	
ONTEC R C5 305 M AT 2xLED 3h M (NM)	5	421	3	M/MN	130	130	27	